Easy Wood Sdn. Bhd. (877688-W) Multi Plank Sdn. Bhd. (913566-M)



EAZYWOOD WPC DECKING SYSTEM MATERIAL (LIST)

VERSION - MARCH 2023

Product Range / Dimensions (W x Thk. X L) mm	Colour Code	Packing (pcs per ctn or bundle)	Remark
WPC DECK BOARD "PROJECT HOLLOW" PE903B	/ EAZYWOOD Rose Wood Balau	100	TIPS recommended for residential usage battens running @ 250 mm c/c (max) most budgetble range.
"PREMIUM RUSTIC HOLLOW" 125 x 25 x 2,000 mm	PE804A, PE103A ,PE801A PE 804B, PE 801B / E/ Teak (804A)	AZYWOOD 100	TIPS recommended for both residential commercial usage battens running @ 250 mm c/c (max).
"PROJECT SOLID" PESO 906A	/ EAZYWOOD Rose Wood Teak	100	TIPS recommended for both residential & commercial usage battens running @ 280 mm c/c (max).
"PREMIUM HOLLOW WITH WO	OOD GRAINED" P 805 / CTWOOD DECK Light Walnut	100	TIPS recommended for both residential & commercial usage battens running @ 250 mm c/c (max).
"PREMIUM PLUS" SOLID / PES	IPE 5 TKS.	100	TIPS recommended for residential & commercial usage battens running @ 250 mm c/c (max) with random wood grained/ colour tone effects
"BAMBOO DECK" SOLID / MF32	21 & DF321 / EAZYWOOD Coffee (DF321) (MF321)	100	TIPS recommended for both residential & commercial usage battens running @ 370 mm c/c (max) with flat or big wave groove surface - pre-finished with water base
BAMBOO EDGING BOARD	Coffee Test (2/1) (DW 031) 001)	10	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to Bamboo Deck

Easy Wood Sdn. Bhd. (877688-W) Multi Plank Sdn. Bhd. (913566-M)



EAZYWOOD WPC DECKING SYSTEM MATERIAL (LIST)

VERSION - MARCH 2023

Product Range / Dimensions (W x Thk. X L) mm	Colour Code	Packing (pcs per ctn or bundle)	Remark
WPC EDGING BOARD 95 x 10 x 3,050 mm	Light Walnut (wood grain coated surface)	10	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to deck board CTDECK / P805
MODEL 7011 (70X10X2.000 mm) (70X11X2.000 mm) (70X11X2.000 mm) (fleak colour)	MODEL 7112 (71X12X2,000 mm) (72X12X2,000 mm) (teak codour)	10	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to
25 x 25 x 3,050 mm	Light Walnut R. Teak (wood grain coated surface)	10	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to deck board CTDECK / P805
54 x 40 x 2,000 mm	Balau	10	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to deck board with "Balau"
WPC EDGE BOARD / PICKE	Rose Balau Teak	100	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to deck board with "Balau" colour - as picket fence too
WPC EDGE BOARD / PICKE	Rose Balau	100	TIPS installed with "direct screw fastening" method, with spacing 300 mm c/c (max) - colour / finishing match to deck board with "Balau" colour - as picket fence too
FIXING ACCESSORIES (DEC	CKING)		
NYLON FASTENER CLIP	BROWN / BLACK (~ 5.0 MM GAP)	100 (per pack)	TIPS installed with stainless steel screws onto the battens for fixing deck boards purposes.
(AS PER SAMPLE)	BROWN (FOR DECK BOARD MODEL CTDECK / P805, WITH ~5.0 MM GAP)	100 (per pack)	TIPS installed with stainless steel screws onto the battens for fixing deck boards purposes.
(AS PER SAMPLE)	CODE 049 BLACK (FOR DECK BOARD MODEL PE 801A, 804A & 103A, WITH ~ 6.0MM GAP)	50 (per pack)	TIPS installed with stainless steel screws onto the battens for fixing deck boards purposes.
(AS PER SAMPLE)	CODE 004 BLACK (FOR DECK BOARD MODEL PE 903A WITH ~6.0MM GAP)	50 (per pack)	TIPS installed with stainless steel screws onto the battens for fixing deck boards

Easy Wood Sdn. Bhd. (877688-W) Multi Plank Sdn. Bhd. (913566-M)

(for install 25 mm thickness batten)



EAZYWOOD WPC DECKING SYSTEM MATERIAL (LIST)

VERSION - MARCH 2023

Product Range / Dimensions (W x Thk. X L) mm	Colour Code	Packing (pcs per ctn or bundle)	Remark
LOCKING FASTENER CLIP (S	STAINLESS STEEL 304) SILVER (~ 5.0 MM GAP)	50 (per pack)	TIPS installed with stainless steel screws onto the battens for controlling the deck boards expansion / shtrinking directions.
FASTENER CLIP (SS 304) (AS PER SAMPLE)	SILVER ** Gap size ~ 2.5 mm upon installed with this clip	100 (per pack)	TIPS installed with stainless steel screws onto the battens only recommended for some specific decking usages. To seek for advices.
BAMBOO DECK FASTENER (CLIP (SS 304), CODE DC1 SILVER ** Gap size ~ 1.5 mm upon installed with this clip	100 (per pack)	TIPS installed with stainless steel screws onto the battens only for Bamboo Deck installation purposes screw spec = M4.2 X 19mm, CSK head, Self-drilling, SS410)
BAMBOO DECK FASTENER O	CLIP (SS 304), CODE DC5 COATED DARK BROWN ** Gap size ~ 6.0 mm upon installed with this clip	100 (per pack)	TIPS installed with stainless steel screws onto the battens only for Bamboo Deck installation purposes screw spec = M4.2 X 19mm, Pan head, Self-drilling, SS410)
STARTER CLIP (SS 304) (AS PER SAMPLE)	SILVER	100 (per pack)	TIPS installed with stainless steel screws onto the battens only recommended for some specific decking usages. To seek for advices.
#8 x 25 mm TAPPING SCREW	((STAINLESS STEEL 304) SILVER (with brown colour screw head) BLACK	100 (per pack)	
(for galvanised steel hollow section ba			
#8 x 30 mm TAPPING SCREW	/ (STAINLESS STEEL 304) SILVER (with brown colour screw head)	100 (per pack)	TIPS special made SS 304 screw for deck boards installation, with screw head in brown colour.
# 10 x 63 mm TAPPING SCRE	W (STAINLESS STEEL 304) SILVER	100 (per pack)	TIPS special made SS 304 screw for deck boards installation, with screw head in brown colour.